

SBC



LB-381LF

VIA Mark Embedded
Board w / VGA / Audio
/ 2LAN

Features :

- Support VIA Mark Processor up to 533MHz
- Equipped with VIA Mark with FSB 133MHz
- Memory Supports PC100/133 SDRAM up to 512MB
- Support Compact Flash
- Support 2 Gigabit LAN ports with Wake-on LAN

Intel®
Communications.
Alliance
Affiliate Member
BRONZE

 **PROTECH SYSTEMS**
It's a right choice

No. 24, Lane 365, Yang Guang St., Nei Hu District, Taipei 114, Taiwan, R.O.C.

Tel: +886-2-8751-1111

Fax: +886-2-8751-1199

Email: sales@protech.com.tw

<http://www.protech.com.tw>




ISO CERTIFIED

9001 | 14001

LB-381LF

VIA Mark Embedded Board w / VGA / Audio / 2LAN



Specifications

System	
CPU Type	VIA Mark Processor
CPU Frequency	533MHz
Chipset	Mark + VT82C686B (FSB : 133MHz)
DRAM	1 x 168-pin DIMM, support PC100/133 SDRAM up to 512MB
BIOS	Phoenix-Award PnP BIOS, with VGA BIOS
Watchdog	16 level Watchdog timer selectable w / Reset / NMI
Power Supply	Support AT / ATX power
Power Requirement	+5V, +12V, -12V (Only +5V with 4.8W power module) (Note: power module does not have enough power to support any add-on cards)
Power Consumption	+5V: 3A / +12V: 0.17A (VIA Eden™ 800MHz) +5V: 2.5A / +12V: 0.14A (VIA Eden™ 400MHz)
Dimension	203mm x 146mm (7.99" x 5.75")
I/O Chipset	
IDE Interface	1 x 40-pin IDE (UDMA 33/66/100) 1 x 44-pin IDE (UDMA 33/66/100)
CF	1 x compact flash slot (IDE)
FDD Interface	1
Bus Interface	PCI slot, PC/104, PC/104+
Serial Port	4 x COM ports, COM1/3/4 for RS232, COM2 for RS232/422/485 (for 16550 compatible type of UART)
Parallel Port	1 x parallel (SPP/EPP/ECP)
IrDA	1 (SIR)

Keyboard	4-pin header with mini DIN cable
Mouse	4-pin header with mini DIN cable
LAN	LAN 1 : Realtek RTL8110S (10/100/1000Mbps) LAN 2 : Realtek RTL8110S (10/100/1000Mbps) Supports Wake-on-LAN with ATX power
Audio	AC '97 Codec, Realtek ALC202A with Line-in / Line-out / MIC
USB	4 x USB 1.1

Display	
Graphic	Built-in VIA 8606, share system memory Supports CRT, TTL & LVDS
LCD Interface	18/24-bit TTL, 18/36-bit LVDS

Environment	
OperationTemp.	0°~60°C(32°~140°F)
Storage Temp.	-40°~85°C(-40°~185°F)
Humidity	Operation humidity 20~90%, Storage humidity 20~95%

Ordering Information

LB-381LF	5.25" CPU Card w VIA Mark 533MHz / VGA / Audio / LAN x 2 (10/100/1000Mbps) (RoHS version)
-----------------	---

Certificate: CE, FCC, CLASS A

PERFORMANCE & POWER CONSUMPTION

CPU Type	Content Creation Winstone 2001	3D Mark 2001 SE	PC Mark 2002	Power Consumption +5V / +12V
VIA Eden™ 800MHz	27.7	270	901	2.9A/0.17A
VIA Eden™ 400MHz	12.9	131	387	2.5A/0.14A

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in MAY. 2006.