



# Ampro COM 840

## Core™ 2 Duo Computer-on-Module

### Blazing Performance, Graphics, Power Management



# COM 840

#### Choose Ampro COM 840 for ...

Modular, ultra high performance applications that require high end graphics.

#### Description

Ampro COM 840 is a small, ultra high performance module, supporting Intel® Core™ 2 Duo processor, with Gigabit Ethernet and high end chipset graphics or x16 PCI Express graphics on the baseboard.

COM 840 is compatible with the COM Express Plug-n-Play initiative for true PICMG COM.0 compliance.



- Up to 4GB DDR2 memory
- True PICMG COM Express COM.0 compliance
- PCI Express, SATA II
- ACPI 2.0 with S3 support
- x16 Graphics on the baseboard
- COM Express Plug-n-Play Initiative

#### For more information, pricing, and details on volume discounts, please call us at 1. 800. 966. 5200 or +1. 408. 360. 0200.

We'll immediately connect you to your local distributor.

Don't see the product you need?

Contact us at 1. 800. 966. 5200 or +1. 408. 360. 0200 for information about our semi-custom and custom solutions.

#### Ordering Information

MODEL	DESCRIPTION
COM-840-R-32	1.6GHz Core™ 2 Duo CPU, 4MB L2 Cache, PCI Express, PCI, LPC
COM-840-L-32	1.6GHz QuickStart Kit (R-32 SBC, 2GB RAM, Software, Documentation, Baseboard, Fansink)
COM-840E-L-32	1.6GHz QuickStart Kit (R-32 SBC, 2GB RAM, Software, Documentation, EBX Baseboard, Fansink)

#### Specifications

##### PROCESSOR

- 1.6GHz Core™ 2 Duo L7500
- Cache – 4MB, 1MB Level 2
- Chipset – Intel GME965/ICH8
- FSB – 800MHz
- System Controllers – PC-compatible DMA and interrupt controllers and timers
- Watchdog Timer

##### MEMORY

- DRAM – Up to 4GB DDR2 667 SODIMM

##### BUS INTERFACE

- PCI Express 5 x1, 1x16, PCI and LPC

##### I/O

- EIDE – Single PCI-bus Enhanced Ultra DMA 66/100 Synchronous IDE Interface supports up to two hard drives
- SATA II – 2 ports
- USB – 8 USB 2.0 ports
- Audio – AC97/HD

##### NETWORK INTERFACE

- Ethernet – Gigabit

##### GRAPHIC INTERFACE

- Intel® GMA X3100, 384MB (DVMT 4.0)
- 3D and 2D engine, HW rotation
- Intel® Clear Video Technology: MPEG-2 HW acceleration and decoding
- WMV9 HW acceleration, sharpness enhancement, film mode detection
- Dual panel display with independent pipes, HD TV support, supports PCIe x16 graphics
- CRT resolution up to 2048 x 1536 @ 60Hz

##### SOFTWARE & DEVELOPMENT TOOLS

- OS Support – Ampro Embedded Linux; Windows® CE 6.0, 5.0, XP, XPe (See Web site for details)
- BIOS – AMI with ACPI 2.0 including S3

##### MECHANICAL

- Size – 95x125mm (3.7x4.9"); COM Express form factor, type II pinout
- Power Requirements (with 2GB RAM, 100% Loaded)
  - 1.77A@12V
- Environmental
  - Temperature (with adequate thermal solution and air flow)
    - Standard: –20° to +70°C
    - Extended: –40° to +85°C
    - Storage: –55° to +85°C
- Board Thickness – .093" (2.36mm)



5215 Hellyer Ave., San Jose, CA 95138 Tel. 408.360.0200 Fax 408.360.0222 sales@ampro.com

NOTICE: The product specifications provided in this datasheet are subject to change without notice. Every effort has been made to ensure the accuracy of this document. Ampro Computers, Inc., makes no warranties, expressed or implied, regarding errors or admissions and assumes no legal liability or responsibility for loss or damage resulting from the use of this document's information. AMPRO is a registered trademark and CoreModule, LittleBoard, Little Board, MightyBoard, MightySystem, MiniModule, ReadyBoard, ReadyPanel and ReadySystem are trademarks of Ampro Computers, Inc. All other trademarks and registered trademarks are the property of their respective owners.

JUN.08

www.ampro.com