


PCM-3601 PCM-3663

56K V.90 Fax/Modem Module

Twin 10/100BASE-T LAN Module



PCM-3601



Features

- 56 K data/fax modem
- Rockwell® modem data pump
- Full duplex
- High-speed 16C550 UART

Specifications

General

- **Control Chipset** Rockwell R6764-61 & L2800
- **Data Mode** K56Flex, V.90, ITU-T, V.34, V.32bis, V.32, V.23, V.22 bis, V.22, V.21, Bell 212A/103
- **Fax Mode** ITU-T G3 fax modulation, T.30, V.17, V.29, V.27ter, V.21 CH2. Support Class 1 & Class 2 command
- **Max. Modem Speed** 56 kbps
- **Max. Fax Speed** 14.4 kbps
- **HardwareError** Correction and data
- **EMC & PTT Support** ITU-T V. 42 & V.42 bis, MNP class 2-5 compression
FCC Part 15 & Part 68/CE/CTR21/JATE (Optional)

Mechanical and Environmental

- **Dimension (L x W)** 96 x 90 mm (3.8" x 3.5")
- **Weight** 0.09 kg (0.198 lb)
- **Temperature** Operating: 0 ~ 70° C (32 ~ 158° F)
Storage: -40 ~ 85° C (-40 ~ 185° F)
- **Operating Humidity** 0% ~ 90% relative humidity, non-condensing

Power

- **Power Supply Voltage** +5 V, ±5 % tolerance on power supply
- **Power Consumption** +5 V @ 350 mA (typical)

Packing List

- 1 x Startup Manual
- 1 x CD-ROM (Manual, Driver, Utility)
- 1 x PCM-3601

Ordering Information

Standard

- **PCM-3601-0000** 56 K V. 90 Fax/Modem Module (FCC Version)
- **PCM-3601-CTR** 56 K V. 90 Fax/Modem Module (CTR21 Version)
- **PCM-3601-JATE** 56 K V. 90 Fax/Modem Module (JATE Version)



PCM-3663



Features

- Supports both Intel® 82559 (optional), 82559ER, TRL-8139
- Supports Wake-on-LAN function
- Supports Half / Full duplex Flow Control
- 10/100BASE-T Ethernet
- Supports Windows® NT 4.0, Windows® 95/98/2000/XP

Specifications

General

- **Chipset** Realtek® 8139 (PCI 10/100Base-T), or Intel 82559/ER (PCI 10/100Base-T)
- **Port** Single/Twin Ethernet port
- **Network Port** 10 Mbps IEEE 802.3, 100 Mbps IEEE 802.3u, 1 x RJ-45
- **Compatibility** PCI version 2.2, 10/100 BASE-T CSMA/CD 10/100 Mbps transceiver

Mechanical and Environmental

- **Dimension (L x W)** 96 x 90 mm (3.8" x 3.5")
- **Weight** 0.09 kg (0.198 lb)
- **Temperature** Operating: 0 ~ 60° C (32 ~ 140° F)
Storage: -40 ~ 85° C (-40 ~ 185° F)
- **Operating Humidity** 0% ~ 90% relative humidity, non-condensing

Power

- **Power Consumption** +5 V @ 800 mA (typical), 0.084 kg (0.185 lb)
- **Power Supply Voltage** +5 V, ±5 % tolerance on power supply

Packing List

- 1 x Startup Manual
- 1 x CD-ROM (Manual, Driver, Utility)
- 1 x PCM-3663

Ordering Information

Standard

- **PCM-3663-00A1E** 10/100Base-T Twin 8139 Ethernet Module (Optional)
- **PCM-3663-01A1E** 10/100Base-T Single 8139 Ethernet Module
- **PCM-3663-02A1E** 10/100Base-T Twin 82559 Ethernet Module
- **PCM-3663-03A1E** 10/100Base-T Single 82559 Ethernet Module (Optional)