
IAC-F694A

·· • Full-Size Dual Socket 370 PIII SBC with VGA/2xLAN



FEATURES

- · Support Intel[®] Pentium[®] III/Celeron[™] Socket 370 CPU, (66/100/133 MHz FSB)
- · VIA 694X/686B chipset
- Three DIMM sockets, support up to 1.5GB SDRAM
- · On board two Intel® 82559 chips, support Dual-10/100M Base-TX Ethernet, on-board RJ-45 connector
- Two PCI IDE ports that support up to four IDE devices and Ultra DMA 100/66/33
- · One FDD port, support up to two floppy devices
- · Two COM ports

ORDERING INFORMATION

IAC-F694A Dual CPU sockets with VGA / 2xLAN

IAC-F694B One CPU socket with VGA / 2x LAN

OPTIONAL



USB Y cable with bracket

Part Number

Item

0800100100002

SPECIFICATION

Support Dual Intel® Pentium® III or one Celeron[™] Processor in Socket 370 (66/100/133 MHz FSB)

Chipset

VIA 694X/686B chipset

BIOS

Award[®] licensed BIOS

System Memory

3 x 168-pin DIMM sockets, support up to 1.5GB SDRAM

VGA

ATI Rage XL, with 8MB Video memory

Ethernet

Intel® 82559 chip, support Dual-10/100M Base-TX Ethernet, on-board RJ-45 connectors

Flash Memory Disk

Reserved socket for DiskOnChip® from M-System, support up to 144 MB flash memory disk

IDE Interface

2 PCI IDE port that support up to 4 IDE devices and Ultra DMA-33/66/100

Floppy Drive Interface

1 FDD port, support up to 2 floppy devices

Serial Port

2 COM ports, 1 x RS-232 and 1 x RS 232/422/

Parallel Port

1 multi-mode parallel port (SPP / EPP / ECP)

Universal Serial Bus

Support 2 USB ports

IR Interface

Support 1 IrDA header Digital I/O

4-bit digital I/O header

Keyboard Connector

5-pin header

Keyboard/Mouse Connector

On board 6-pin mini-DIN PS/2 mouse & keyboard RTC Internal RTC with Li battery

Watchdog Timer

16-level time-out intervals (by software program)

Power Consumption

+5V@8.5A (Pentium® III 1GHzx2, 512MBx3 SDRAM) +12V:350mA, -12V:30mA

Operating Temperature 0°C~60°C

Humidity $5\% \sim 95\%$ RH, non-condense

Dimensions 338.5 x 122 mm (13 1/4" x 4 5/6")

Net Weight 300g (0.66 pounds)