

# RDC-1191-C1

19" single port KVM



## FEATURES

- Industrial grade-A LCD TFT active-matrix color panel
- On-Screen Display allows for easy adjustment of color, brightness, contrast, position, and shape of the display
- Standard D-sub 15-pin VGA input connector
- Space saving design - ultra-low 1U (1.75") flip-up display enclosure
- Unique mechanical design to maximize mountable space
- Come with sliding rail and mounting kit for easy to integrate in any 19" cabinet
- Supports AT/XT, PS/2, UNIX, Sun, and Macintosh

## ORDERING GUIDE

Standard

RDC-1191-C1

19" single port KVM

## GENERAL

Display area	376.3 (H) x301.1 (V) (19.0-inch diagonal)
Pixel Pitch	0.294 (H) x0.294 (V)
Number of Pixels	1280 (H) x1024 (V)
Contrast Ratio	600:1
Color	16.7M (8 bits/colors)
Brightness (cd/m <sup>2</sup> )	250 (Typ.)
On-Screen Display	Contrast, Brightness, H/V Position, H/V Size, H-scaling, Auto-adjust, Color Temp.(9300, 6500, User), Red-Gain, Blue-Gain, Green-Gain, Gamma, Recall, Phase, Channel, OSD exit
Power Consumption	Power Consumption: 44 Watts
Power Supply	Power Supply: AC 100-240V Universal
Power	12VDC adapter
Input Signal	RGB Analog
VGA	15-pin D-Sub
Keyboard / Mouse	PS/2
Keyboard / Keypad	88-key keyboard and integrated Touch Pad
Numeric keys	17-key numerical key pad
Hot Key Control	OSD Hot Key
Temperature	0~50in operating; -20~60 in storage
Humidity	10~85% in operating; 10-90% in storage
Dimensions	20.27in(D) x 19.05in(W) x 1.7in(H)
Weight	22.3lb/10.1kg