

Industrial Single Board Computer

5.25" Embedded Miniboard

LS-574

Support 2nd Generation Intel® Core™ i7/i5/i3 CPU
with DDRIII SO-DIMM, CRT, DVI, LVDS, Gigabit LAN,
PCI Express mini card, SATAI/III, Audio, COM, LPT



| | |
|-----------------------------|---|
| Form Factor | 5.25-inch Embedded Miniboard |
| CPU | 2 nd Generation Intel® Core™ i7, Core™ i5, Core™ i3 and Celeron® Mobile Processor Package type: rPGA988B |
| Memory | 2 x DDRIII SO-DIMM 1066/1333/1600 MHz up to 16GB |
| Chipset | Intel QM67 Express chipset |
| Real Time Clock | Chipset integrated RTC with onboard lithium battery |
| Watchdog Timer | Generates a system reset with internal timer for 1min/s ~ 255min/s |
| Power Management | Supports ACPI 3.0 compliant |
| Serial ATA Interface | 4 x serial ATAI interface with 300MB/s transfer rate 2 x serial ATAIII interface with 600MB/s transfer rate |
| Integrated Graphics | Intel® Core™ integrated HD Graphics Technology |
| VGA Interface | Onboard DSUB15 connector for VGA interface |
| LVDS Interface | Onboard 24-bit dual channel LVDS connector with +3.3V/+5V/+12V supply |
| DVI interface | Chrontel CH7318 Transmitter with 26-pin DVI connector |
| Audio Interface | Realtek ALC888 HD Audio |
| LAN Interface | 6 x Intel 82574L Gigabit LAN |
| GPIO Interface | Onboard programmable 8-bit Digital I/O interface |
| Extended Interface | 2 x PCIE mini card socket, 1 x SIM socket |
| Internal I/O Port | 1 x PS/2, 4 x RS232, 1 x RS232/422/485, 1 x Parallel, 1 x SMBUS, 1 x GPIO, 6 x USB2.0 ports, 1 x IrDA, 1 x DVI , 1 x LVDS, 4 x Serial ATAI, 2 x Serial ATAIII, 1 x Front panel Audio and 1 x CDIN |
| External I/O Port | 6 x LAN ports, 1 x VGA port, 2 x USB2.0 ports, 1 x RS232, , 1 x DC connector |
| Power Requirement | Standard 20-pin ATX power supply or 9~24V full range DC Input |
| Dimension | 203 mm x 146 mm |
| Temperature | Operating within 0~60 centigrade Storage within -20~85 centigrade |
| Ordering Code | |
| LS-574TXD | Intel PGA988B+ QM67 Onboard VGA, LVDS, DVI, LAN, USB2.0, HD Audio, SATAI ,SATAIII, SMBUS, LPC, SIM, GPIO and PCI Express mini card. |

Taiwan Commate Computer Inc.

19F, NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

Website:www.commell.com.tw

FAX: +886-2-26963911

E-mail:info@commell.com.tw

 **COMMELL**

Stage For Your Success