
Industry-Proven Solenoids



EB200 Series

The EB200 series industrial solenoids are available in standard base and side mountings and have stainless steel saddle type retainers. They are available in stacking widths of 1/2, 3/4, 1 and 1-1/4 inches. Standard versions available for 115, 230, 460V, 60 Hz.

Features include:

- 1/2 inch stroke
- 115, 230, and 460V, 60 Hz models
- 2 to 10 pound pull or push force
- Standard side and base mounting
- 1-1/2" long stainless steel round loose push pin available at additional charge
- Captive pin is also available at additional cost. (Pin has head or shoulder which serves to hold it in place in the solenoid.)
- -10°C to 30°C ambient environment
- Rated for continuous duty

EB450 Series

Series EB450 solenoids are available with pull and push force of 7 to 11 pounds and a stroke up to 1 inch. The EB450 series is rated for continuous duty. Available in stacking widths of 3/4 and 1 inch. They are designed with stainless steel saddle stops. All models have through holes in stack for mounting.

Features include:

- 1 inch stroke
- 115, 460V, 60 Hz standard
- 7 to 11 pound pull or push force
- -10°C to 30°C ambient environment
- Rated for continuous duty

EB600 Series

Series EB600 solenoids are available in pull or push versions with stacking widths of 1/2, 3/4 and 1. Designed with stainless steel saddle stops and have .5 inch stroke maximum. All models have through holes in stack for mounting.

Features include:

- .5 inch stroke
- 115, 230, 60 Hz
- 3 to 8 pound pull or push force
- -10°C to 30°C ambient environment
- Rated for continuous service

EB710 Series

The EB710 series industrial solenoids are designed for use in Class B insulation systems with ambient temperatures ranging from -10°C to 30°C with occasional excursions to 40°C. They are available in stacking widths of 1/4, 1, 1-1/4 and 2 inches and feature universal mounting brackets. They can be equipped with special coils to enable them to function under a wide range of severe industrial environments.

Features include:

- 10 to 30 pound push or pull force
- Stainless steel saddle-type retainers
- 115, 230, and 460, 60 Hz model
- 1 inch stroke
- -10°C to 30°C ambient environment
- Rated for continuous duty

The EB710 series is intended to replace the EB700 series.

*Call or write for your free 18-page
Namco Solenoid catalog.*
