

ASB200-810



Features

- Fanless system supports IBASE ECX810
- Onboard Intel® EP80579 integrated processor, 600MHz / 1GHz
- Suitable for fanless platforms requiring multiple LAN ports
- Rear panel I/O for USB, VGA, COM, KB/mouse, LAN and DC-in jack
- Wall mount kit included
- Available in black color

Specifications

System Mainboard	ECX810
CPU Type	Intel® EP80579 Processor
System Speed	600MHz / 1GHz
Memory	1x DDR2 533/667/800 SO-DIMM, Max. 2GB
Construction	Aluminum & Steel
Chassis Color	Black
Front Panel External I/O	Power LED, HDD LED, Reset button, Power on/off button, 2x USB, 2x Audio jack
Rear Panel External I/O	1x VGA, 1x USB ports, 1x COM ports, 3x RJ-45 connectors, CF Socket, KB/MS connector, DC-in jack
Storage	1x 2.5" HDD
Power Supply	60W power adaptor
Mounting	Desktop or wall mount
Dimensions	240mm(W) x 162mm(D) x 58.7mm(H)

Environmental

Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	CFD: 5 grms / 5~500Hz / random operation HDD: 0.25 grms / 5~500Hz / random operation

Ordering Information

ASB200-81006M	Fanless System w/ ECX810-ASB06 Embedded Board w/ ID810 VGA, w/ 60W power adapter, 2.5" HDD holder
ASB200-81010M	Fanless System w/ ECX810-ASB10 Embedded Board w/ ID810 VGA, w/ 60W power adapter, 2.5" HDD holder



Remarks: 1. ODM/OEM is available
2. Specifications are subject to change without prior notice.

- 1 Motherboards
- 2 Disk-Size SBCs
- 3 CPU Modules
- 4 PC/104 Plus
- 5 CPU Card
- 6 Embedded Systems
- 7 Network Security Appliance