

PONy Express[™] 16

Universal Transport Platform for Access Networks



The PONy (Passive Optical Network over wavelengths) Express 16 is the first transport platform to use a Passive Optical Network (PON) architecture to break the access bottleneck. Using Dense Wave Division Multiplexing (DWDM), the PONy Express 16 provides cost-effective access to business parks, campuses, and multi-dwelling unit/multi-tenant units over a shared network infrastructure without sacrificing security or limiting bandwidth. Up to 16 customers can be simultaneously connected with each having up to 1Gbps dedicated, symmetrical bandwidth. Operationally, each Optical Network Terminal (ONT) is "colorless" which eliminates the sparing issue that plagues traditional DWDM systems and provides "plug-n-play" system provisioning. The PONy Express 16 is integrated into other ADC products such as the OmniReach® FTTX Fiber Distribution Hub FDH3000S providing a compelling solution unique to the industry.

lerin			

OT G CT IT	ig information		
Description		Catalog Number*	
OLT Shelf and Common	19" Rack Mountable Chassis for Optical Line Terminating Equipment	PNY16-OLT Shelf	
Equipment	Software license for OLT (1 PNYr OLT)	PNY16-OLT SW	
	Main Control Unit (MCU)	PNY16-MCU	
	Broadband Lightsource and Upstream AWG Mux/Demux	PNY16-BMU	
	Variable speed fan unit containing 3 fans	PNY16-OLT Fan	
	-48VDC Power Supply Unit	PNY16-PSU	
OM Shelf and Module	Chassis	PNY16-OM Shelf	
	Module	PNY16-1310-OM	
CO Line Cards	1.25 Gbps Ethernet Line Card for OLT	PNY16-OCU-1250	
	125 Mbps Ethernet Line Card for OLT	PNY16-OCU-125	
Subscriber Equipment	1.25Gbps Ethernet Subscriber Unit	PNY16-ONT-1250	
	125Mbps Ethernet Subscriber Unit	PNY16-ONT-125	
Remote Equipment	Downstream AWG Mux/Demux	PNY16-RN	