

Daughter Board



BR-6061R

Serial Port Card

NEW




Specifications

Applicable Models	Serial Port Card
Input Interface	Low PIN Count 2 x 10 pin(2.0 pitch)
Component	Fintek F81216
Output Connector	4 Port UART 1 port UART on edge (COM A). 3 port box-header on board COM A support RS232 COM B/C/D support; w/ RS232/422/485 or w/12V, 5V (Option)
Dimension	50mm x 89mm

BD-4010R

TPM Module

NEW



Specifications

Applicable Models	Trusted Platform Module(TPM)
Interface	Low Pin Count
TPM chip	Infineon SLB9635 TT 1.2
Connector	1x2.0mm pin-header 1x2.54mm pin-header
Dimension	31.3mm x 29.7mm(12.32" x11.69")

BR-3010R

Audio Daughter Board

NEW



Specifications

Applicable Models	Protech Audio Card transfer interface
Component	Realtek ALC888 family
Function	High Definition Audio
Input Connector	1 x wafer connector (2 x 6 pin)
Output Connector	3 x audio jack, 1 x wafer connector (2 x 5 pin)
Dimension	56 mm x80 mm, 2.20" x 3.15"

DMP-1030LF

PC/104+ Module w/PCMCIA



Specifications

Applicable Models	PC/104+ Interface
Component	TI PCI1520PDV
Function	PCI bus. PCMCIA type II/III (32-bit card bus)
Input Connector	Standard PC/104+ connector
Output Connector	1 x PCMCIA type III socket
Dimension	96 mm x 96 mm (3.74" x 3.74")