

Product Specifications

DisplayPac-OP

12.1", 15", 17" NEMA 12 Panel-Mount Computers with FCC, CE & UL Approvals



Display Specifications

- Display 12.1" 800x600 AMTFT, 340 nit;
15" 1024x768 AMTFT, 250 nit;
17" 1280x1024 AMTFT, 250 nit

Touchscreen Specification

- Type 5-wire resistive, serial

Computer Specifications

- CPU Socket 370 Intel Tualatin up to 1.26 GHz, Pentium III 66/100/133 up to 1 GHz, Celeron 66/100 up to 1.2 GHz, Socket 478 Pentium 4 CPU up to 2.8 GHz (15" and 17" units only)
- Memory One 168-pin DIMM socket, SDRAM up to 512M
- Display Integrated VGA/LCD controller, 2D/3D GUI engine, 4X AGP, video memory up 64M (sharing system memory)
- Dual display VGA and RCA TV-out ports supporting Windows® O/S, mirroring and multiple dual display modes
- Ethernet 10/100BaseT
- Audio AC'97 Audio Codec (Line-in, Line-out, and MIC-in)
- VGA port One VGA interface
- USB ports Up to four USB ports
- Serial ports Four ports (3x RS-232, 1x RS-232/485); COM3 used for touchscreen
- Parallel One port supporting SPP/EPP/ECP

- Floppy One external interface with DC power (12.1" and 15" units)
- Keyboard/mouse One PS/2 keyboard, one PS/2 mouse
- Digital I/O Two input, two output with one RJ-12 phone jack
- Watchdog timer 64 time intervals
- Expansion slots One PCI and one PCI/ISA shared; two PCI (17")
- Front bezel Aluminum bezel (black or silver) standard; small bezel, big bezel (steel, beige) optional

Peripheral & Storage Specifications

- Power supply 150W ATX (200W P4); input range 100 - 230 VAC @ 47 - 63 Hz
- Storage devices 3.5" IDE hard drive, one slim-type CD-ROM, one floppy drive

Mechanical & Environmental Specifications

- Construction Heavy-duty steel; chassis color: beige
- Mounting Panel mount with brackets
- Dimensions 12.1" 14.37" x 11.57" x 4.07" (WxHxD)
365 mm x 294 mm x 103.5 mm
15" 16.06" x 13.03" x 4.39"
408 mm x 331 mm x 111.5 mm
17" 17.48" x 14.80" x 5.19"
444 mm x 376 mm x 130 mm
- Certifications FCC, CE, UL, NEMA 12
- Temperature 0° - 50°C (operating)
-20° to 70°C (storage)
- Relative humidity 10 - 90% non-condensing
- Shock and vibration 10G peak acceleration; 5 - 7 Hz, 0.1" double amplitude displacement 17 - 500 Hz, 1.5G acceleration peak to peak

Options

- Storage device DVD, CD-ROM-R/W
- Power supply DC 90W, 9 - 16V or 18 - 36V
- Flash drive Solid state memory; call for details
- Operating system Windows 2000, 9x, ME, NT, NTE, XP, XPE, Linux

Ordering Information

PAC-OP-<Display>-<CPU-speed>-<Memory>-Options

Specifications may change without notice due to component changes.



Embedded Systems

GE Fanuc Embedded Systems Information Center — Greenville Location

Computer Dynamics, 7640 Pelham Road, Greenville, SC 29615

Phone: (864) 627-8800 • Fax: (864) 675-0106 • www.gefanuc.com/ipc

© 2004 GE Fanuc Automation Americas, Inc. All rights reserved. Celeron, Intel and Pentium are registered trademarks of Intel Corporation. Windows is a registered trademark of Microsoft Corporation. All other brands or names are the property of their respective holders. Specifications are subject to change without notice. Reproduction or copying of images is prohibited without the express written permission of GE Fanuc Embedded Systems, Inc.07/04 GFA-429M