



QR Code - Scan to Link



# CPB4712

## CompactPCI Processor Blade

**CompactPCI**



Diversified Technology's CPB4712 PICMG 2.16-compliant packet switched backplane (PSB) processor blade combines high performance with low power for telecom and Internet IP-based applications.

The CPB4712 features the low voltage (LV) high performance Dual-Core Intel® Xeon processors at speeds ranging from 1.67GHz up to 2.0GHz with 2MB L2 cache. The CPB4712 is based on the Intel® 3100 chipset with 667MHz front side bus. System memory of up to 4GB is supported via two DDR2-400 SO-DIMMs. Onboard are dual 100/1000Mbps Ethernet ports routed according to PICMG 2.16, one 10/100/1000Mbps Ethernet port available at the front panel, one PMC/XMC site (64-bit/133MHz and x4 PCIe), High Speed USB, and a serial port. The CPB4712 also includes a two-stage watchdog timer for enhanced system reliability.

The CPB4712 has a PCI bridge to the backplane and can therefore operate in any slot of a PICMG® 2.16-compliant Packet Switched Backplane (PSB). PICMG® 2.9 system management is also supported via a satellite management controller.

Part of DTI's PlexSys family of PSB products, the CPB4712 was validated in DTI's PlexSys-4, 4U general purpose, carrier grade computing platform with CSB4240 Ethernet level 2/3 switch. The IPMI 1.5-compliant Baseboard Management Controller (BMC), when used with a chassis management module, supports a comprehensive, protected lights-out management scheme.

The CPB4712 system/peripheral processor blade is a cost effective choice for application developers addressing high performance, converging Telecom and Internet IP-based markets such as VPN switches, media gateways, 2.5G/3G wireless, server clusters, IP DSLAM and voice/video/data servers.

### Product Features

#### Form Factor

PICMG® 2.16 PSB System/Peripheral Processor Blade

#### CPU/Cache

Dual-Core Intel® Xeon® LV processor with max speeds of 2.0GHz and 2MB L2 cache

#### Bus Interface

- Intel® 3100 Chipset
- 667MHz Front Side Bus; 32-bit/33MHz CompactPCI Bus interface

#### Memory

- Two DDR2-400 SO-DIMM sockets
- 512MB to 4GB of total DDR2 memory

#### I/O

- Two 100/1000 Ethernet Interfaces on 2.16 Switched Fabric
- 10/100/1000 Ethernet Interface on Front Panel
- Serial ATA
- 1 PMC/XMC Site
- 2 High Speed USB Ports
- Serial Port

#### BIOS

AMI BIOS

#### Physical Dimensions:

9.2" x 6.3" x 0.8"

#### OS Support

Windows® Vista, Windows® XP with SP2, Red Hat Linux®, Solaris

#### Warranty

Parts and labor covered for 2 years

**CPU / Cache**

- Dual-Core Intel® Xeon® LV processor (1.67GHz or 2.0GHz)
- 32KB internal L1 cache; 2MB 64-bit on-die L2 Cache

**Bus Interface**

- Intel® 3100 Chipset
- 667MHz Front Side Bus; 32-bit/33MHz CompactPCI Bus interface
- 5V/3.3V CompactPCI signaling as host
- Supports one onboard 64-bit/133MHz 3.3V PMC card
- Supports one onboard x4 PCIe XMC card

**Memory**

- Two DDR2-400 SO-DIMM sockets
- Memory must be registered and ECC-capable for integrity
- 512MB to 4GB of total memory
- PC2-3200, PC2-4200, or PC2-5300 Memory at 400MHz

**Data Path**

- 64-bit/667MHz on CPU and memory bus
- 32-bit/33MHz on off-board CompactPCI bus
- 64-bit/133MHz on onboard PCI bus
- x4 PCIe

**Flash Memory**

- 1MB Flash for BIOS
- USB Flash Disk (UDISK)

**Ethernet**

- Two 100/1000 Ethernet Interfaces on 2.16 Switched Fabric
- One 10/100/1000 Ethernet Interface on faceplate

**Peripherals and I/O Interface**

- 2.5" SATA HDD drive mounted on RTM
- 64-bit/133MHz PMC site
- x4 PCIe XMC
- Hardware Monitor

**I/O Interface**

| I/O Interface    | Front Panel   | Rear Panel |
|------------------|---------------|------------|
| COM 1            | RJ-45         | N/A        |
| USB #1           | USB Connector | N/A        |
| USB #2           | USB Connector | N/A        |
| 100/1000 ENET    | N/A           | J3         |
| 10/100/1000 ENET | RJ-45         | N/A        |
| Serial ATA       | N/A           | J3         |
| PCIe             | N/A           | J3         |
| Video            | Via PMC       | Via PCIe   |
| USB #3           | N/A           | J3         |
| USB #4           | N/A           | J3         |

Note: Rear Panel I/O accessible with DTI's CRT4712 and CRT4712E

**Clock / Calendar**

Real-time clock with battery backup CMOS RAM

**Supervisory**

Two-stage programmable watchdog timer drives interrupt on 1st stage and hardware reset on 2nd stage

**Interoperability**

- Validated to operate in a PICMG 2.16-compliant system platforms
- 3rd party PSB products

**OS Compatibility**

Windows® Vista, Windows® XP with SP2, Red Hat Linux®, Solaris

**BIOS**

- AMI BIOS
- PCI 2.2
- ACPI 1.0b and 2.0
- SMBIOS 2.3.1
- PnP 1.0a
- Serial console redirection
- Multi-boot Support (Floppy, HD, CD, USB, Network)
- Legacy USB Support
- S.M.A.R.T. Support

**BIOS cont'd**

- Pop-up Boot Menu
- PXE 2.1 Boot Rom

**Management**

- Integrated IPMI compliant satellite management controller
- Communicates with system management BMC or host processor
- Compliant with PICMG 2.9

**Mechanical**

- 9.2 in. x 6.3 in. 0.8 in. (233.35 mm x 160 mm x 20.32 mm)
- 6U x 4HP
- Conforms to PICMG 2.0 R3.0 (Core), 2.9 (Management) 2.12 (SW interoperability), 2.15 (PTMC) and 2.16 R1.0 (PSB) specifications

**Power Requirements**

Input Power Rails: +12V, +5V, +3.3V

With CPB4712, CRT4712, and 1GB memory  
1.67GHz or 2.0GHz

Max Power Dissipation 54.9 W

| ICC typical | +12V  | N/A    |
|-------------|-------|--------|
|             | +5.0V | 5.65 A |
|             | +3.3V | 4.79 A |

**Environmental**

**Operating** (designed to meet)

- Temperature: 0° to 50°C full speed, up to 65°C with speed throttling
- Humidity (RNC): up to 98%
- Altitude: 13,000ft @ 34°C / 25,000ft @ 25°C
- Vibration: 5-100Hz @1g
- Shock: 10g half-sine shock for 11ms, 3 in each direction

**Storage and Transit** (in approved packaging)

- Temperature: -40°C to 70°C
- Altitude: 15240m / 50,000ft
- Shock: 40" free fall, 20g half-sine shock for 6ms, 100 in each direction
- Vibration: 30 min, random 5-20Hz @ 1m2/s3; 20-200Hz with -3dB

**Reliability and Serviceability**

- MTBF: 251,306 hours @ 25°C (performed using Issue 6, Method I, Case 3 of the Bellcore IR Program)
- 2 year limited warranty

**Regulatory Compliance**

- Designed for NEBS/ETSI Compliance
- Designed for CE Certification
- UL/cUL 60950-1; EN/IEC 60950-1
- EMI/EMC: FCC 47 CFR Part 15 Class B; EN 55024:1998, EN 61000-3-2, EN 61000-3-3, EN 55022:1998, CISPR22:1997, AS/NZS3548:1995

**Ordering Information**

**CPB4712/1670 \***

CPB4712 Processor Blade with 1.67GHz Low Voltage (LV) Intel® Xeon® Processor and 2MB L2 cache

**CPB4712/2000 \***

CPB4712 Processor Blade with 2.0GHz Low Voltage (LV) Intel® Xeon® Processor and 2MB L2 cache

\* Indicates long life-cycle support

**Options**

- DDR2 400 Memory Capacity (512MB, 1GB, 2GB)
- CRT4712 or CRT4712E Rear Transition Module
- USB Flash Disk Capacity (128MB, 1GB, 4GB)
- PMC Integration
- XMC Integration

All products are shipped FOB factory (MS). Specifications subject to change without notice. Trademarks are the property of their respective owners. (C) Copyright 2008-2011 by Diversified Technology, Inc. All rights reserved.



www.dtims.com/cpci

1.800.443.2667

476 Highland Colony Parkway • Ridgeland, MS 39157

