


» MICROSPACE® MSM-e0/-N «



MICROSPACE®



PC/104-Plus™ SBC with the new AMD™ embedded G-Series processor

- » Most powerful graphics for long-term available PC/104-Plus™ designs
- » For extremely compact multimedia applications
- » Up to 4GB DDR3 SO-DIMM RAM, integrated ATI Radeon graphics, 3D performance: 10x D510 (3DMark06)

MICROSPACE® MSM-e0/-N

PC/104-Plus™ SBC w. new AMD™ embedded G-Series processor

Technical Information

	MSM-e0	MSM-e0-N
Processor/Performance	AMD™ embedded T44R 1.2GHz Single Core	AMD™ embedded T24L 1.0GHz Single Core
Chipset	AMD™ FCH A55E	AMD™ FCH A55E
Bus	PC/104-PCI 32 bit 33MHz 4 Slots, PC/104-ISA 16 bit	PC/104-PCI 32 bit 33MHz 4 Slots, PC/104-ISA 16 bit
Memory	Up to 4GB LVDDR3-1066 1x SO-DIMM	Up to 4GB LVDDR3-1066 1x SO-DIMM
Graphics	AMD Radeon™ HD 6250	-
Video Memory	Up to 384 MB shared video memory	-
LCD Interface	Up to 1920x1200 24bpp	-
CRT Interface	Up to 1920x1200 30bpp	-
DDI	Display port, DVI, HDMI	-
Sound	HD Audio line-out, mic-in, SPDIF out/in	-
SATA HDD-Interface	2x SATA 150/300/600 with RAID 0,1 support	2x SATA 150/300/600 with RAID 0,1 support
COM1/2 / COM2/3	2x RS232/2x UART	2x RS232/2x UART
USB	4x USB 2.0	4x USB 2.0
Ethernet	2x Gbit LAN	1x Gbit LAN
Available I/Os	LPC, SPI	LPC, SPI
Standard Temperature	0°C to + 60°C	0°C to + 60°C
Dimensions	90mm x 102mm	90mm x 102mm
Special Features	8x GPIO 4x A/D 2x D/A PWM Boot from LAN, Watchdog, bootable micro SD card slot, ECO Mode (minimal power consumption)	8x GPIO 4x A/D 2x D/A PWM Boot from LAN, Watchdog, bootable micro SD card slot, ECO Mode (minimal power consumption)

Ordering Information

Article	Part-No.	Description
MSM-e0	802400	PC/104™ SBC CPU T44R with (graphic, sound, press-fit connector options: PCI, ISA), 2x Gbit LAN
MSM-e0-N	802410	PC/104™ SBC CPU T24L, 1x Gbit LAN
RAM 1GB DDR3 SODIMM	802365	Option MSM PC/104 SBC with 1GB DDR3 memory
RAM 2GB DDR3 SODIMM	802366	Option MSM PC/104 SBC with 2GB DDR3 memory
RAM 4GB DDR3 SODIMM	802367	Option MSM PC/104 SBC with 4GB DDR3 memory
PC/104 PCI connector	802313	Option PC/104 PCI press-fit connector
PC/104 ISA connector	802312	Option PC/104 ISA press-fit connector
MSM-e0 Heat Spreader Kit	802408	Heat spreader, screw set included
MSM-PC104 Passive Cooler Kit	802314	Heat sink without fan including assembly material
MSM-PC104 Active Cooler Kit	802316	Heat sink with fan including assembly material
MSM-PC104 CK	802040	Cable kit including: Interfaces: Line-In/Out or Mic-In, S/PDIF, 1Gb Ethernet Cables: Power, USB, VGA, COM single, SATA, LAN, audio

CORPORATE OFFICES

Europe, Middle East & Africa

Oskar-von-Miller-Str. 1
85386 Eching/Munich
Germany
Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 279
info@kontron.com

North America

14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

Asia Pacific

17 Building, Block #1, ABP.
188 Southern West 4th Ring Road
Beijing 100070, P.R.China
Tel.: + 86 10 63751188
Fax: + 86 10 83682438
info@kontron.cn