



Features

- ✓ 915GME with Pentium M or Celeron M
- ✓ 14-bit Interruptible Digital Input
- ✓ 15-bit High Current Output
- ✓ Italian JAMMA Interface
- ✓ Dual 256KB Battery Backup SRAM with Battery Low Event Logger
- ✓ 6W Stereo Amplifier
- ✓ PCI Express x16 Slot
- ✓ 4-bit Intrusion Logger Input

Specification

System

CPU	Socket for Intel Pentium M & Celeron M
Chipset	Intel 915GME + ICH6M
Front Side Bus	400/533MHz
Memory	2 x 240-pin DIMM socket support 533/667MHz Dual Channel DDR2 SDRAM up to 2GB
Battery	<ul style="list-style-type: none"> • 1 x 220mAh battery for system RTC • 2 x 140mAh re-chargable batteries for SRAM, Second RTC, Intrusion Logger
Real Time Clock	1 x system RTC and 1x secured RTC
Fan Connector	2 x 12V fan connector

Video

Graphic Controller	Intel 915GME integrated GMA 900 graphic controller
Video Memory	DVMT 3.0, Maximum 128MB shared
Video Interface	<ul style="list-style-type: none"> • 2 x VGA (1 x DB15, 1 x pin header) • 1 x Dual Channel 18-bit LVDS (Pin header)

PCI Express Slot	1 x PCI Express x16 slot
-------------------------	--------------------------

Storage

IDE	1 x IDE (40-pin)
SATA	1 x SATA I port
CF	1 x Compact Flash Type I/II socket support UDMA

Communication

Ethernet	1 x 100Mbps RJ45 with LED, Intel 82562ET PHY
USB	6 x USB2.0 (2 x external port, 4 x pin header)
Serial Port	<ul style="list-style-type: none"> • 3 x RS-232 (1 x DB9, 2 x pin header) • 2 x ccTalk/RS-232

Audio

Output	Stereo
Amplifier	6 Watts per channel
Volume Channel	Left channel

Other Feature

PS/2	1 x PS/2
Hardware	<ul style="list-style-type: none"> • CPU voltage temperature
Monitoring	<ul style="list-style-type: none"> • CPU and fan speed
WatchDog Timer	Software programmable 1~255 sec.
Indicator	HDD and Power LED

Gaming Function

I/O Interface	Italian JAMMA Interface
Digital Input	<ul style="list-style-type: none"> • 14 x optical isolated input • State change interrupt
Digital Output	15 x 1000 mA digital output
Readable DIP Switch	2 x 8-bit DIP switch
GPIO (TTL Level)	20 bits (optional)
Timer	4 x 16-bit timers with time out interrupt

Gaming Function

Battery backup SRAM	<ul style="list-style-type: none"> • 2 x 256KB (Optional 2 x 512KB) • 140 mAh rechargeable battery • Battery voltage low log and voltage readback 1K Bytes
EEPROM	-
Jurisdiction Chip	-
Intrusion Logger	<ul style="list-style-type: none"> • 1 x chassis intrusion switch + 3 bits on golden fingers • 10 events with time stamps • 140 mAh rechargeable battery • battery voltage low log and voltage readback
Smart Card Reader	-
Reel Mechanism Control	-
Smart Hard Meter	-
Random Number Generator	16 bits
Security	iButton socket and ProtectU

Power Requirement

Power Input	5V (+/-5%) and 12V (+/-5%) input on golden finger
Power Consumption	

Software

OS Support	Windows XP/XP Embedded, Linux
Software Development Kit	<ul style="list-style-type: none"> • Device driver • Application Program Interface (API) • Demo program

Mechanical & Environment

Dimension	184.3mm x 227.78mm (7.26" x 8.97")
Weight	Net: 373g (0.9Lb)
Operating Temp.	0~60°C (32~140°F)
Storage Temp.	-20~80°C (-4~176°F)
Relative Humidity	0 to 90% @ 40°C, non-condensing
Safety	CE, FCC class A

Packing List

- 1 x ACE-B5296
- 1 x Driver CD
- 1 x Quick user manual

Ordering Information

Optional CPU	<ul style="list-style-type: none"> • Intel Pentium M 760 2.0GHz, FSB 533MHz and 2MB L2 cache • Intel Pentium M 745 1.8GHz, FSB 400MHz and 2MB L2 cache • Intel Celeron M 370 1.5GHz, FSB 400MHz and 1MB L2 cache
Accessory	PS/2 keyboard and mouse connector