



RPS-300DC48

300W Redundant DC-DC AT Power Supply (Horizontal Type)

P/N: RPS-300DC48							
Input Range	DC -38 ~ -58V/Max. 15A						
Output Voltage	+5 V 25A (2A Min)	+3.3 V --	+5 V/3.3 V Total --	+12 V 10A	-5 V 1A	-12 V 4A	+5 Vsb --
MTBF(hours)	100,000						
Safety	UL/CSA/TUV/CE						
Power Module Part No. (Accessories)	RPM-300DC48						
Compatible with Advantech Products	IPC-622-30RD-01						



RPS-300

300W Redundant AC-DC AT Power Supply (Horizontal Type)

P/N: RPS-300							
Input Range	AC 90 ~ 132V/180 ~ 264V @ 47 ~ 63 Hz, selectable 6.0/3.5 A						
Output Voltage	+5 V 30A (3A Min)	+3.3 V --	+5 V/3.3 V Total --	+12 V 12A (1A Min)	-5 V 0.5A	-12 V 0.5A	+5 Vsb --
MTBF(hours)	100,000						
Safety	UL/CSA/TUV/CE						
Power Module Part No. (Accessories)	RPM-300						
Compatible with Advantech Products	IPC-622-300R/IPC-622-300R-01/IPC-622BP-300RB/IPC-622P4-300R						



RPS-250-SADT/RPS-250-SDTB

230W Redundant AC-DC AT Power Supply

P/N: RPS-250-SADT/RPS-250-SDTB							
Input Range	AC 90 ~ 130V/180 ~ 260V @ 47 ~ 63 Hz, selectable 6.0/3.0 A						
Output Voltage	+5 V 25A (4A Min)	+3.3 V --	+5 V/3.3 V Total --	+12 V 12A (1A Min)	-5 V 1A	-12 V 1A	+5 Vsb --
MTBF(hours)	110,000						
Safety	CSA/TUV						
Power Module Part No. (Accessories)	RPM-250						
Compatible with Advantech Products	RPS-250-SADT: IPC-615/IPC-6908 RPS-250-SDTB: IPC-610/IPC-6608						