

List Price \$114.00 USD

Availability **Stock Item:** This item is normally stocked in our distribution facility.**Technical Characteristics**

Number of Poles	3-Pole
Ampere Rating	10A
Lock Method	Not Lockable
Actuator Type	Key
Height	4.50 Inches
Connection Type	(2) 0.5 Inch NPT (Conduit Entrance)
Enclosure Rating	NEMA 4/4X/12 - IP67
Contact Operation	Slow Break (Make before Break)
Enclosure Type	Water tight, Dust tight and Corrosion resistant (Indoor/Outdoor)
Approvals	UL Listed File Number: E164353 CCN NKCR - CSA Certified File Number: LR4408794 Class 3211 03 - CE Marked
Contact Configuration	1 N.O.(staggered)/2 N.C.
Depth	1.18 Inches
Enclosure Material	Plastic
Orientation	Actuating Key: Field Selectable - Electromagnet: Via conduit entrance
Maximum Voltage Rating	300VAC
Operating Temperature Range	-13 to 158 Degrees F
Terminal Type	Screw Clamp
Type	XCSTA

Shipping and Ordering

Category	22411 - Limit Switches, Heavy Duty, IEC, Type XCKJ
Discount Schedule	T
Article Number	785901786108
Package Quantity	1
Weight	0.46 lbs.
Availability Code	S
Returnability	Y

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.