

Industrial Single Board Computer

5.25" Embedded motherboard LE-575

Intel Atom processor
Onboard VGA , LVDS , Giga LAN ,
Mini PCI , PCI , USB2.0 , SATA
HD Audio and Compact Flash socket



Form Factor	5.25" Embedded motherboard
CPU	Intel Atom N270 processor 1.6GHz Package type: FCBGA8 , Front side bus: 533MHz
Memory	One 200-pin DDR2 SO-DIMM SDRAM up to 2GB Non-ECC, unbuffered memory supported
Chipset	Intel 945GSE & ICH7M
Real Time Clock	Chipset integrated RTC with onboard lithium battery
Watchdog Timer	Generates a system reset with internal timer for 1min(sec) ~ 255min(sec)
Power Management	ACPI 1.0 compliant, supports power saving mode
VGA Interface	Intel integrated extreme GMA 950(Graphic Media Accelerator) Technology
Video Memory	Up to 224MB shared with system memory
LVDS interface	Onboard 18-bit dual channel LVDS connector Optional: Secondary 18/24-bit dual channel LVDS interface with +3.3V/+5V/+12V supply.(LE-575X2 Only)
DVI Interface	Optional: 26-pin DVI connector Header for DVI. (LE-575XD Only)
Solid State Disk	IDE supports 44-Pin Disk On Module with +5V power supply One Compact Flash Type II socket
Serial ATA interface	2 x serial ATA interface with 150MB/s transfer rate
Audio Interface	Intel ICH7-M integrated with Realtek ALC888 2-CH HD Audio
LAN Interface	4 x Intel 82574L Gigabit Ethernet controllers
GPIO interface	Onboard programmable 8-bit Digital I/O interface
Extended Interface	2 x Mini-PCI socket 、 1 x PCI Slot 、
Internal I/O Port	1 x IrDA , 1 x GPIO , 1 x AUDIO , 1 x CDIN , 1 x LVDS , 6 x USB2.0, 1 x RS232/RS422/485 , 1 x LCD Inverter , 2 x SATA , 1 x HDTV , 4x COM 1 x LPT , 1 x Slim FDD , 1 x PS/2 , 1 x SPDIF , 1 x SMBUS
External I/O Port	4 x LAN ports , 2 x USB2.0 ports , 1 x Serial Port , 1 x VGA , 1 x DC jack
Power Requirement	Standard 24-pin ATX power supply(20-pin is compatible) Or 9~24V full range DC input
Dimension	146mm x 203mm
Temperature	Operating within 0~60 centigrade Storage within -20~85 centigrade

Ordering Code

LE-575X	Intel Atom processor with onboard VGA, Mini PCI, Audio , SATA , GLAN , USB2.0 , CF , GPIO , 18-bit LVDS
LE-575XD	Same as LE-575X and with DVI
LE-575X2	Same as LE-575X and with secondary 18/24-bits LVDS

Taiwan Commate Computer Inc.

8F, NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

Website:www.commell.com.tw

FAX: +886-2-26963911

E-mail:info@commell.com.tw



Stage For Your Success