

Ampro ReadyBoard™ 800

Pentium® M EPIC Single Board System

Ultra High Performance, Low Power, Easy Interface



ReadyBoard 800

Choose Ampro ReadyBoard 800 for...

High volume, compact embedded applications that need ultra high CPU and I/O performance, fanless operation and low cost.

Description

Ampro ReadyBoard 800 SBC gives you a choice of ultra high performance, low-power Centrino® processors with high speed I/O to match. It includes Gigabit Ethernet, USB 2.0, and high performance graphics in an easy to use compact industry standard form factor SBC.

- Up to 1 GB of DDR memory
- Ampro BIOS extensions
- Dual Ethernet – Gigabit and 10/100BaseT
- 4 Serial, 4 USB 2.0 ports
- PCI-104 expansion
- ReadyBox™ enclosure available
- ReadySystem™ turn-key systems available



Ordering Information

MODEL	DESCRIPTION
RBI-800-K-01	600MHz QuickStart Kit (Q-01 SBC, 512MB RAM, Cable Kit, Software, Documentation)
RBI-800-K-10	1.0GHz QuickStart Kit (Q-10 SBC 512MB RAM, Cable Kit, Software, Documentation)
RBI-800-K-21	1.4GHz QuickStart Kit (Q-21 SBC 512MB RAM, Cable Kit, Software, Documentation)
RBI-800-Q-01	600MHz ULV Celeron M CPU, PCI-104, dual Ethernet, Video, 4 COM
RBI-800-Q-10	1.0GHz ULV Celeron M CPU, PCI-104, dual Ethernet, Video, 4 COM
RBI-800-Q-21	1.4GHz LV Pentium M CPU, PCI-104, dual Ethernet, Video, 4 COM
RBI-ALL-W-01	Cable Kit
MM3-ISA-Q-01	MiniModule ISA, PCI-104 to PC/104-Plus Bridge

For more information, pricing, and details on volume discounts, please call us at 1.800.966.5200 or +1.408.360.0200. We'll immediately connect you to your local distributor.

Don't see the product you need? Contact us at 1.800.966.5200 or +1.408.360.0200 for information about our semi-custom and custom solutions.

Get Started Today. Order a QuickStart Kit Now.

Specifications

PROCESSOR

- Choice of
 - 1.4GHz LowVoltage Pentium® M 738 (Dothan)
 - 1.0GHz Ultra LowVoltage Celeron® M 373 (Dothan)
 - 600MHz Ultra LowVoltage Celeron M
- Cache – 2MB or 512kB Level 2
- Chipset – Intel 855GME/ICH4M
- FSB – 400MHz
- System Controllers – PC-compatible DMA and interrupt controllers and timers
- Real Time Clock – Battery-backed RTC/CMOS
- Watchdog Timer
- Powerfail Reset – Triggers when input voltage drops below predetermined thresholds

MEMORY

- DRAM – Up to 1GB PC2700 DDR333 SODIMM

BUS INTERFACE

- PCI-104 (PCI)
- PCI-104 to PC/104-Plus bridge through optional MiniModule™ ISA card

I/O

- EIDE – Single PCI-bus Enhanced Ultra DMA 33/66/100 Synchronous IDE Interface supports up to two hard drives
- CompactFlash on secondary IDE
- Serial – 4 ports, 2 are RS232/422/485
- Parallel – EPP/ECP bidirectional port shared with floppy interface
- Floppy – Supports 1 or 2 drives shared with parallel port
- USB – 4 USB 2.0 ports (four root hubs)
- Keyboard/Mouse – PS/2 interface
- GPIO – Eight digital I/O pins
- Audio – AC97 speaker, mic, headphone

NETWORK INTERFACE

- Ethernet – One Intel 82541 (1000BaseT) and one Intel 82551ER (10/100BaseT)

VIDEO INTERFACE

- Controller – Integrated Intel Extreme Graphics 2
 - AGP 128-bit 3D engine
 - Supports resolutions to 2048x1536
 - Up to 64MB UMA Frame Buffer
 - Dual channel LVDS
 - Supports 3.3V and 5V flat panels

SOFTWARE & DEVELOPMENT TOOLS

- OS Support – See Web site for current listings
- BIOS – General Software 5.3 with Ampro extensions

MECHANICAL

- Size – 114.3x165.1mm (4.50x6.50"); EPIC 1.0 Form Factor
- Power Requirements (w/128MB RAM, 100% Loaded)
 - 1.4GHz 3.8A @5V
 - 1.1GHz 3.5A @5V
 - 600MHz 3.0A @5V
- Environmental
 - Operating temperature: 0° to 60°C
 - Storage temperature: -20° to 75°C



AMPRO

2515 Hellyer Ave., Ste. 110, San Jose, CA 95138 Tel. 408.360.0200 Fax 408.360.0222 sales@ampro.com

NOTICE: The product specifications provided in this data sheet are subject to change without notice. ©2005 Ampro Computers, Inc. All rights reserved. Ampro is a registered trademark and CoreModule, MiniModule, LittleBoard, Little Board, EnCore, ReadyBoard, ReadyBox, ReadySystem and MightyBoard are trademarks of Ampro Computers, Inc. All other trademarks and registered trademarks are the property of their respective owners. DS-RB800 5K 0805

www.ampro.com