Network Security Appliance

FWA7304 NEW

Entry Desktop VIA based Network Security Appliance with 4 FE LAN



>> Features:

- Supports 4 FE Realtek LAN ports
- Supports 400MHz~1GHz VIA
- Eden™-V4 NanoBGA2 low power
- DDR2 SO-DIMM x 1, up to 1GB
- Mini-PCI slot, Compact Flash socket
- Low power and fanless, Aluminum enclosure
- Optional Hardware LAN Bypass function on ETH 0 & 1
- RoHS Compliant

FWA7304 Specifications

CPU: VIA Eden™-V4 400MHz/1GHz Chipset: VIA CN700, 400MHz FSB Memory: DDR2 SO-DIMM x 1, up to 1GB

Network Interface: Supports 4 x Realtek RTL8100C FE LAN ports

Expansion Slot: Onboard Mini-PCI slot

Storage: Onboard Type 2 Compact Flash socket x 1, 2.5"HDD x 1

USB: Two USB 2.0 ports on rear panel

Serial I/O: One DB-9 console connector on rear panel
One COM 2x5 pin connectors on board

VGA: Pin header on board

LED Indicator: Power/Status/Alarm indication LEDs

Power Supply: 20W power adaptor

Environmental|Mechanical:

Operating Temperature: 0 ~ 40°C Storage Temperature: -20 ~ 70°C

Relative Humidity: 10 ~ 90% (non-condensing)

Dimensions: 35mm (H) x 156mm (W) x 225mm (D)

Certification: CE/FCC

Ordering Information

FWA7304-NB400

Entry Desktop, VIA Eden™-V4 400MHz, 4 FE LANs, without LAN bypass

FWA7304-NB1G

Entry Desktop, VIA Eden™-V4 1GHz, 4 FE LANs, without LAN bypass

FWA7304-1G

Entry Desktop, VIA Eden™-V4 1GHz, 4 FE LANs, with LAN bypass

Optional Accessories

FWA 7304 2.5"HDD Kit

2.5" HDD bracket for FWA7304 series

Remarks

* Add (-R) after the model name for RoHS-compliant version when ordering.





BI