

G7S600-B-G

Intel[®] 865G chipset ATX System Board

PROCESSOR

- Intel[®] processor
 - Intel[®] Pentium[®] D
 - Intel[®] Pentium[®] 4
 - Intel[®] Celeron D
 - Hyper-Threading Technology
 - 800MHz/533MHz system data bus
- Processor socket: Socket 775

CHIPSET

- Intel[®] chipset
 - Intel[®] 865G Graphics Memory Controller Hub (GMCH)
 - Intel[®] 82801EB I/O Controller Hub (ICH5)

SYSTEM MEMORY

- Four 184-pin DDR DIMM sockets
- Supports dual channel (128-bit wide) memory interface
- Supports up to 4GB system memory
- Synchronous operation with processor system bus
 - PC2700/PC3200 (DDR333/DDR400) with 800MHz FSB CPU. DDR333 will run at 320MHz memory frequency when used with 800MHz FSB CPU.
 - PC2100/PC2700 (DDR266/DDR333) with 533MHz FSB CPU
- Supports non-ECC (x64) DIMM using 128Mb, 256Mb or 512Mb
- Supports unbuffered DIMMs

BIOS

- Award BIOS
- 4Mbit flash memory

ENERGY EFFICIENT DESIGN

- Supports ACPI specification and OS Directed Power Management
- Supports ACPI STR (Suspend to RAM) function
- Wake-On-Events include:
 - Wake-On-PS/2 Keyboard/Mouse
 - Wake-On-USB Keyboard
 - Wake-On-Ring (external modem)
 - Wake-On-LAN
 - RTC timer to power-on the system
- System power management supported
- CPU stopped clock control
- Microsoft[®]/Intel[®] APM 1.2 compliant
- Soft Power supported - ACPI v1.0a specification
- AC power failure recovery
- Auto power-on function
- Watchdog timer function

ONBOARD GRAPHICS FEATURES

- Graphics memory
 - Shares 1MB/4MB/8MB/16MB/32MB of the system memory in DOS mode
 - Uses Dynamic Video Memory Technology (DVMT) in Windows mode
- Graphics controller
 - Core frequency of 266MHz
 - 350MHz integrated 24-bit RAMDAC
 - Analog display up to 2048x1536 @ 60Hz refresh
 - 3D setup and render engine - Discrete, Triangles, Strips and fans
 - Per pixel perspective corrected texture mapping
 - Software DVD at 30fps, full screen
- 2D graphics features
 - Optimized 256-bit BLT engine
 - 32-bit alpha blended cursor
 - Programmable 3-color transparent cursor
- 3D graphics features
 - 200 megapixels/sec fill rate
 - Maximum 3D resolution: 1600x1200x32 @ 85Hz
 - Flat and Gouraud shading
 - 16- and 24-bit Z-buffering and 16- and 24-bit W-buffering
 - Vertex and programmable pixel fogging and atmospheric effects
 - Double and triple render buffer

ONBOARD AUDIO FEATURES

- Realtek audio CODEC
- 16-bit stereo full-duplex codec with 48KHz sampling rate
- High quality differential CD input
- True stereo line level outputs
- S/PDIF-out interface
- 6-channel audio output

ONBOARD LAN FEATURES

- Realtek RTL8110SC Gigabit LAN PCI interface
- Integrated power management functions
- Supports 10Mbps, 100Mbps and 1Gbps data transmission
- IEEE 802.3 (10/100Mbps) and IEEE 802.3ab (1Gbps) compliant

IDE INTERFACE

- Supports up to UltraDMA 100Mbps hard drives
- PIO Mode 4 Enhanced IDE (data transfer rate up to 14MB/sec.)

SERIAL ATA INTERFACE

- Supports two SATA (Serial ATA) interfaces which are compliant with SATA 1.0 specification (1.5Gbps interface)

REAR PANEL I/O PORTS

- 1 mini-DIN-6 PS/2 mouse port
- 1 mini-DIN-6 PS/2 keyboard port
- 1 DB-25 parallel port
- 1 DB-9 serial port
- 1 DB-15 VGA port
- 4 USB 2.0/1.1 ports
- 1 RJ45 LAN port
- 3 audio jacks: mic-in, line-in and line-out

I/O CONNECTORS

- 2 connectors for 4 additional external USB 2.0/1.1 ports
- 1 connector for 1 external serial port
- 1 Digital I/O connector
- 1 Digital I/O power connector
- 1 front audio connector for external line-out and mic-in jacks
- 1 CD-in internal audio connector
- 1 speaker-out connector
- 1 S/PDIF-out connector
- 1 connector for IrDA interface
- 2 Serial ATA connectors
- 2 IDE connectors
- 1 floppy connector
- 1 24-pin ATX power connector
- 1 4-pin 12V ATX power connector
- 1 Wake-On-LAN connector
- 3 fan connectors

EXPANSION SLOTS

- 1 AGP slot
- 6 PCI slots

COMPATIBILITY

- PCI 2.2 and AC '97 compliant
- Intel AGP version 3.0

TEMPERATURE

- 0°C to 60°C

HUMIDITY

- 10% to 90%

PCB

- 4 layers, ATX form factor
- 30.5cm (12") x 24.4cm (9.6")

SAFETY

- UL, cUL, FCC Class B, CE

REAR PANEL I/O PORTS

